



MODEL		RWEYQ6TYM	RWEYQ8TYM	RWEYQ10TYM	RWEYQ12TYM
Combination units		—	—	—	—
		—	—	—	—
		—	—	—	—
Power supply		3-phase 4-wire system, 380-415 V/380 V, 50/60 Hz			
Cooling capacity	kcal/h	13,800	19,300	24,100	28,800
	Btu/h	54,600	76,400	95,500	114,000
	kW	16.0	22.4	28.0	33.5
Power consumption	kW	2.58	3.86	5.43	7.33
Casing colour		Ivory white (5Y7.5/1)			
Dimensions(HxWxD)		mm 1,000 × 780 × 550			
Compressor	Type	Hermetically sealed scroll type			
	Motor output	kW 1.9	2.8	3.7	4.7
Refrigerant piping connections	Liquid	mm ϕ 9.5 (Flare)			ϕ 12.7 (Flare)
	Suction gas *1	mm ϕ 19.1 (Brazing)		ϕ 22.2 (Brazing)	
	High and low pressure gas	mm ϕ 19.1 (Brazing) *2		ϕ 22.2 (Brazing) *2	
Water piping connections	Water inlet	PT1 1/4B intenal thread			
	Water outlet	PT1 1/4B intenal thread			
	Drain outlet	PS1/2B intenal thread			
Machine weight (Operating weight)	kg	146 (148)		147 (149)	
Sound level	dB(A)	49	50	51	53
Operation range (Inlet water temp.)	°C	10 to 45			
Capacity control	%	23-100		19-100	
Refrigerant charge	Type	R-410A			
	Charge	kg 3.5		4.2	



MODEL		RWEYQ14TYM	RWEYQ16TYM	RWEYQ18TYM	RWEYQ20TYM	RWEYQ22TYM	RWEYQ24TYM
Combination units		RWEYQ6TYM	RWEYQ8TYM	RWEYQ8TYM	RWEYQ10TYM	RWEYQ10TYM	RWEYQ12TYM
		RWEYQ8TYM	RWEYQ8TYM	RWEYQ10TYM	RWEYQ10TYM	RWEYQ12TYM	RWEYQ12TYM
		—	—	—	—	—	—
Power supply		3-phase 4-wire system, 380-415 V/380 V, 50/60 Hz					
Cooling capacity	kcal/h	33,000	38,500	43,300	48,200	52,900	57,600
	Btu/h	131,000	153,000	172,000	191,000	210,000	229,000
	kW	38.4	44.8	50.4	56.0	61.5	67.0
Power consumption	kW	6.44	7.72	9.29	10.9	12.8	14.7
Casing colour		Ivory white (5Y7.5/1)					
Dimensions(HxWxD)		mm (1,000 × 780 × 550) × 2					
Compressor	Type	Hermetically sealed scroll type					
	Motor output	kW	1.9 + 2.8	2.8 × 2	2.8 + 3.7	3.7 × 2	3.7 + 4.7
Refrigerant piping connections	Liquid	φ12.7 (Flare)		φ15.9 (Flare)		φ19.1 (Flare)	
	Suction gas *1	mm φ28.6 (Brazing)					
	High and low pressure gas	φ28.6 (Brazing) *2					
Water piping connections	Water inlet	(PT1 1/4B) × 2 internal thread					
	Water outlet	(PT1 1/4B) × 2 internal thread					
	Drain outlet	(PS1/2B) × 2 internal thread					
Machine weight (Operating weight)	kg	146 × 2 (148 × 2)		146 + 147 (148 + 149)		147 × 2 (149 × 2)	
Sound level	dB(A)	53		54		55	56
Operation range (Inlet water temp.)	°C	10 to 45					
Capacity control	%	23-100		20-100		19-100	
Refrigerant charge	Type	R-410A					
	Charge	kg	3.5 + 3.5		3.5 + 4.2		4.2 + 4.2



MODEL		RWEYQ26TYM	RWEYQ28TYM	RWEYQ30TYM	
Combination units		RWEYQ8TYM	RWEYQ8TYM	RWEYQ10TYM	
		RWEYQ8TYM	RWEYQ10TYM	RWEYQ10TYM	
		RWEYQ10TYM	RWEYQ10TYM	RWEYQ10TYM	
Power supply		3-phase 4-wire system, 380-415 V/380 V, 50/60 Hz			
Cooling capacity		kcal/h	62,600	67,400	72,200
		Btu/h	248,000	268,000	287,000
		kW	72.8	78.4	84.0
Power consumption		kW	13.2	14.7	16.3
Casing colour		Ivory white (5Y7.5/1)			
Dimensions(HxWxD)		mm	(1,000 × 780 × 550) × 3		
Compressor		Type			Hermetically sealed scroll type
		Motor output	kW	2.8 × 2 + 3.7	2.8 + 3.7 × 2
Refrigerant piping connections		Liquid			φ19.1 (Flare)
		Suction gas *1			φ34.9 (Brazing)
		High and low pressure gas			φ34.9 (Brazing) *2
Water piping connections		Water inlet			(PT1 1/4B) × 3 intenal thread
		Water outlet			(PT1 1/4B) × 3 intenal thread
		Drain outlet			(PS1/2B) × 3 intenal thread
Machine weight (Operating weight)		kg	146 × 2 + 147 (148 × 2 + 149)	146 + 147 × 2 (148 + 149 × 2)	147 × 3 (149 × 3)
Sound level		dB(A)	55	56	
Operation range (Inlet water temp.)		°C	10 to 45		
Capacity control		%	21-100	20-100	19-100
Refrigerant charge		Type			R-410A
		Charge	kg	3.5 + 3.5 + 4.2	3.5 + 4.2 + 4.2



MODEL		RWEYQ32TYM	RWEYQ34TYM	RWEYQ36TYM	
Combination units		RWEYQ10TYM	RWEYQ10TYM	RWEYQ12TYM	
		RWEYQ10TYM	RWEYQ12TYM	RWEYQ12TYM	
		RWEYQ12TYM	RWEYQ12TYM	RWEYQ12TYM	
		RWEYQ12TYM	RWEYQ12TYM	RWEYQ12TYM	
Power supply		3-phase 4-wire system, 380-415 V/380 V, 50/60 Hz			
Cooling capacity		kcal/h	77,000	81,700	86,900
		Btu/h	305,000	324,000	345,000
		kW	89.5	95.0	101
Power consumption		kW	18.2	20.1	22.0
Casing colour		Ivory white (5Y7.5/1)			
Dimensions(HxWxD)		mm	(1,000 × 780 × 550) × 3		
Compressor		Type	Hermetically sealed scroll type		
		Motor output	kW	3.7 × 2 + 4.7	3.7 + 4.7 × 2
Refrigerant piping connections		Liquid	φ19.1 (Flare)		
		Suction gas *1	φ34.9 (Brazing)		
		High and low pressure gas	φ34.9 (Brazing) *2		
Water piping connections		Water inlet	(PT1 1/4B) × 3 intenal thread		
		Water outlet	(PT1 1/4B) × 3 intenal thread		
		Drain outlet	(PS1/2B) × 3 intenal thread		
Machine weight (Operating weight)		kg	147 × 3 (149 × 3)		
Sound level		dB(A)	57	58	
Operation range (Inlet water temp.)		°C	10 to 45		
Capacity control		%	19-100		
Refrigerant charge		Type	R-410A		
		Charge	kg	4.2 + 4.2 + 4.2	